



System Comparison Guide	Compact System	SD System	HD-PLUS System
	Starting bundle <b>\$329.98</b>	Starting bundle <b>\$379.98</b>	Starting bundle <b>\$439.98</b>
<b>Tractors by HP Range (Engine Gross)</b>			
Subcompact Tractors <35 HP * (See exception list on page below)	✓	✓*	✓*
Tractors 35 to 70 HP <sup>1</sup> (Compact W/ Cat 1 Implements ONLY)	✓ <sup>1</sup>	✓	✓
Tractors 71 to 100 HP	✗	✓	✓
Tractors >100 to 165 HP	✗	✗	✓
<b>Implement Types by Category</b>			
3-Point Hitch Implements - Cat 1	✓	✓	✓
3-Point Hitch Implements - Cat 2	✗	✓	✓
3-Point Hitch Implements - Cat 3	✗	✗	✓
Any Drawbar Implements - Pull Type	✗	✗	✓
<b>Other Key Features</b>			
Dual Pin Types	1 Mounted Locking Pin + 1 Safety Bolt (Ball Detent) - <b>GOOD</b>	1 Mounted Locking Pin + 1 Plunger Pin (Wedge Tip) - <b>BETTER</b>	2 Mounted ¼ -Turn Locking Pins - <b>BEST</b>
Non-Mounted, Stand-Alone Pin REQUIRED During Operation	✓	✓	OPTIONAL
QPQ <sup>SM</sup> Surface Finish	✓	✓	✓
Small 1000 RPM Implement Coupler Adaptable for 540 RPM PTO	-	-	✓
1 Year Warranty (extendable to 3 years)	✓	✓	✓
Available to Authorized Dealer	✓	-	✓
<b>Key Operating Specs</b>			
Diameter of Coupler Flange	3 ¾"	4 ¾"	4 ¾"
Combined Thickness of Coupler Flanges When Coupled	¾"	⅞"	1"
Added Length To PTO Driveline	5.0"	5.0"	5.0"
# of Open-Plate™ Slots w/ Connected Studs	3	4	4
Degrees of Rotation To Couple System	30°	18°	18°
Distance of Rotation To Complete Coupling System	1"	¾"	¾"
Weight (Both Couplers)	5.60 lbs.	8.25 lbs.	8.60 lbs.
Max Torque (Ft. Lbs.)	1500	2100	3100
Shear Stress (Yield Strength)	120 ksi	125 ksi	135 ksi

Questions? Call us at (833) 444-5465



## Tractor Models Limited to the Compact System ONLY

- Kubota BX Series →
- Kubota B Series
- Kubota LX Series
- Kioti CS Series
- Yanmar SA Series
- John Deere 2520 (2005 - 2013)
- New Holland Workmaster 25 S
- Massey Ferguson 25, 1010, 1020, 1030, 1035
- Cub Cadet 6284D
- Bad Boy 3026
- LS MT122, MT125, MT225
- Mahindra 1526, 1626, 2126

### PTO Link® Compact System Lift Arm Stabilizer Plate Replacement Kit



**For Kubota BX  
Tractors ONLY**

**Tractors with a PTO output shaft length of  
3 inches or shorter must use the PTO Link® Compact System,  
as it is the only compatible option.**

**Use the Compact System with a 3-point hitch (category 1)  
implements only.**

**Questions? Call us at (833) 444-5465**